

# **MATERIAL SAFETY DATA SHEET**

## **D-METHYL LACTATE**

MSDS NO.004

## **SECTION 1- MATERIAL/COMPANY IDENTIFICATION**

Chemical Name Methyl-D(R)-2-Hydroxy propionate
Company Name Musashino Chemical (China) Co., Ltd.

Address No.66 Chunfeng Rd. Economic & Technological Development

Zone of Yichun, Jiangxi. 336000 China

Charge Department for MSDS Safety Management Department

 Responsibility for MSDS
 Fan Gui-Zeng

 Tel.
 +86-795-3156266

 Fax
 +86-795-3196986

 Emergency Tel.
 +86-795-3156282

#### **SECTION 2- HAZARDS IDENTIFICATION**

Class Name 3.3 High flash-point flammable liquid

Human Health Effects Vapor may cause irritant of eyes, mucous membranes and skin

#### **SECTION 3- COMPSITION/INFORMATION ON INGREDIENTS**

Chemical name Methyl-D(R)-2-Hydroxy propionate

Component 98% up

Formula CH<sub>3</sub>CH(OH)COO CH<sub>3</sub>

Molecular Weight 104.1

CAS No. 17392-83-5

UN Dangerous Goods No. 3272

#### **SECTION 4- FIRST AID MEASURES**

General advice Show this safety data sheet to the doctor in attendance.

Skin contact Immediately remove all contaminated clothing, including

footwear. Flush skin and hair with plenty of water or tepid water.

Eye contact Immediately hold eyelids apart and flush eyes with plenty of

water at least 15minutes. If irritation persists, call a physician.

Inhalation Immediately remove to fresh air.

If breathing is difficult, give oxygen, call a physician.

Ingestion If swallowed, drink plenty of water or salt water.

If in doubt, Call a physician immediately.

#### **SECTION 5- FIRE FIGHTING MEASURES**

Specific hazards Flammable. Can be happen explosion in fire and high

temperature. Chemical reaction with strong oxidizing agents.



Burning produces irritant fumes

Extinguishing media Remove a source of fire. Use a fire extinguisher. Cool the

container with plenty of water. Standing upwind side and wear

breathing apparatus.

Water, carbon dioxide (CO<sub>2</sub>), foam, dry power.

#### **SECTION 6- ACCIDENTAL RELEASE MEASURES**

Personal precautions Prepare extinguishing media before starting on cleaning.

Wear protective clothing and self-contained breathing

apparatus. Avoid contact with skin and eyes. Take person refuge in upwind side. Keep person out the place. Keep away from

heat and flames promptly.

Environmental precautions Prevent further leakage or spillage, Prevent product from

entering drains

Methods for cleaning up In case of small quantities of leakage, pack a absorbent

material into container after absorbing spilled material. Clean

up the leaked place with plenty of water.

In case of large quantities of leakage, Tighten rope around the leakage place. Flush spilled material into container after leading to suitable retaining areas stopping the fluid by sand and the

like. Clean up the leaked place with plenty water.

## **SECTION 7- HANDLING AND STORAGE**

Handling Caution not to generate firer, as to fire, static electricity, and

spark.

Take account of preventing the materials from leak.

Wear protective clothing to prevent from contacting and inhalating

the materials.

Storage Avoid direct rays of the sun.

Keep container tightly closed.

Keep away from high temperature substances.

Use earth and anti-explosive electric-apparatus in storage

areas.

Packaging material Polyethylene plastic containers etc.

#### **SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering measures to

reduce exposure

Ensure adequate ventilation, especially in confined areas.

Personal protection equipment

Wear personal protective equipment. Avoid contact with skin and eyes. Especially if necessary, wear organic gas

mask, air mask, or self-contained breathing apparatus.



Hygiene measures Set up safety shower, hands washer and eyes washer nearby

handling the materials. Indicate the positions distinctly. When

using, do not eat, drink or smoke. Remove and wash

contaminated clothing before re-use.

# **SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** Transparent, Clear liquid having an characteristic odor.

144.8°C **Boiling point** 

3.93 KPa (20°C) Vapor pressure

Melting point -66℃

Flash point 54.5°C (closed up)

385℃ Auto ignition temperature

**Explosion limits** Lower 2.2 vol% 1.080~1.100g/ml Density (20°C)

Solubility Freely soluble in water, most organic solvents

3.1 mPa.s @25°C Viscosity

#### **SECTION 10- STABILITY AND REACTIVITY**

Stability Stable at normal conditions. Hazardous polymerization does

not occur.

Conditions to avoid Avoid temperatures above 54.5°C

Materials to avoid Avoid oxidizing agents, acid, alkaline, water,

Hazardous decomposition CO, CO<sub>2</sub>

products

#### **SECTION 11- TOXICOLOGICAL INFORMATION**

Acute toxicity LD50 >5000 mg/ kg bw. (rat, oral)

 $LC50 > 5.73 \text{ g/m}^3 \text{ (rat)}$ 

#### **SECTION 12- ECOLOGICAL INFORMATION**

Mobility Completely soluble, readily biodegradable and hydrolyses, no

hazardous polymerization.

Chemical Oxygen Demand 1.50 g O<sub>2</sub>/g

(COD)

Biochemical Oxygen Demand

 $0.94 \text{ g } O_2/\text{g}$ 

 $(BOD)_{20}$ 

## **SECTION 13- DISPOSAL CONSIDERATIONS**

Waste from residues/unused

products

Burn up absorbent sand gradually in the opened incinerator after absorbing the materials, or burn up the materials directly

in the incinerator through atomizer.



Contaminated packaging Decontaminate empty containers with water, dilute with water

and flush to waste system. Recycle containers if possible.

Further information Treatment, storage, transportation, and disposal must be in

accordance with local regulations.

# **SECTION 14- TRANSPORTATION INFORMATION**

China Dangerous Goods No. 33602
UN Dangerous Goods No. 3272
Packaging Class III
Packaging label 3

Sticking properly on label, indicating material name, lot No., net

weight etc

Further information The materials transportation by vehicles, the sender serves

deliverers with instructions for safe handling.

In transportation confirm leak less of the container, and load the materials not to upset, fall and damage. Secure preventing the

load from falling.

#### **SECTION 15- REGULATORY INFORMATION**

Class Name 3.3 High flash-point flammable liquid

R-Phrases R10-Flammable.

R36/37-Irritation to eyes and respiratory system.

S-Phrases S24-Avoid contact with skin.

China Regulations Chemical Dangerous Substances Safety Management Regulatory

Chemical Dangerous Substances Safety Management Detailed

Rules And Regulatory

Safety Using Chemical Regulatory In Working Site

### **SECTION 16- OTHER INFORMATION**

Revision Date 2020/06/01

LC50 Median lethal concentration

LD50 Median lethal dose